



Puncte de lucru

CRAIOVA	Str. Libertatii Nr. 2	TEL: 0251-30.60.30	FAX: 0251-30.60.31
BUCURESTI (Berceni)	Str. Securilor Bl. 17A, Sc. 1 Ap. 1	TEL: 021-332.18.92	FAX: 021-332.18.92
BUCURESTI (Jilava)	Str. Giurgiului Nr. 53	TEL: 021-405.04.83	FAX: 021-405.04.82
BACAU	Com. Margineni Nr. 191	TEL: 0234-21.10.55	FAX: 0234-21.10.55
CLUJ NAPOCA	Str. Giordano Bruno Nr. 31	TEL: 0264-43.58.94	FAX: 0264-43.58.94
TIMISOARA	Str. Palmierilor Nr. 19	TEL: 0256-20.75.04	FAX: 0256-20.75.04
BAIAMARE	Str. Grivitei Nr. 32	TEL: 0262-20.63.12	FAX: 0262-20.63.13
CONSTANTA	Str. Tabla Butii Nr. 2	TEL: 0241-60.61.60	FAX: 0241-60.61.62
BRASOV	Str. Feldioarei Nr 31R1	TEL: 0268-44.08.50	FAX: 0268-44.00.58

Web: <http://www.mst.ro>
Email: office@mst.ro

Sediul Social: CRAIOVA – Str. Traian Lalescu, Bl. a1, Sc. 1, Ap. 2
Reg. Com. J16/238/1999 C.I.F. – RO11682019 Capital Social – 50.000
IBAN: RO 29 BRMA 0170 0173 0620 0000 – Banca Romaneasca S.A. Suc. Craiova



Cablu coaxial RG6

Dimensiuni fizice cablu coaxial RG6

Componente	Invelis Standard (Dia.mm)	Invelis Triplu (Dia.mm)	Patru Invelisuri (Dia.mm)
Conductor Interior	1,02	1,02	1,02
Dielectric	4,57	4,57	4,57
Primul Invelis	4,75	4,75	4,75
Invelis exterior	6,90	7,06	7,54
Sufa Otelita	Simplu	1,30	1,30
	Dublu	1,83	1,84

Caracteristici mecanice cablu coaxial RG6

Puterea minima de rupere a sufei	Dia. 1.30mm 82kgf
	Dia. 1.83mm 166kgf

Caracteristici electrice cablu coaxial RG6

Impedanta	75Ω	
Eficacitatea Invelisului (Ydb)	55MHz	68
	300MHz	70
	1000MHz	70
SRL(Ydb)	VHF	20
	UHF	20

Atenuare (20°C, db/100m)

55MHz	5,3
211 MHz	10,0
270 MHz	11,0
300 MHz	11,6
330 MHz	12,3
400 MHz	13,6
450 MHz	14,4
550 MH	16,2
750 MHz	19,0
870 MHz	20,6
1000 MHz	22,2

